

527468  
N91-11690

CLUTTER FILTER DESIGN CONSIDERATIONS  
FOR  
AIRBORNE DOPPLER RADAR DETECTION OF WINDSHEAR

p 30

Ernest G. Baxa, Jr.  
Clemson University  
Clemson, SC 29634-0915

ABSTRACT

The problem of clutter rejection when processing down-looking Doppler radar returns from a low altitude airborne platform is a paramount problem. With radar as a remote sensor for detecting and predicting windshear in the vicinity of an urban airport, dynamic range requirements can exceed 50 dB because of high clutter to signal ratios. This presentation describes signal processing considerations in the presence of distributed and/or discrete clutter interference. Previous analyses have considered conventional range cell processing of radar returns from a rigidly mounted radar platform using either the Fourier or the pulse-pair method to estimate average windspeed and windspeed variation within a cell. Clutter rejection has been based largely upon analyzing a particular environment in the vicinity of the radar and employing a variety of techniques to reduce interference effects including notch filtering, Fourier domain line editing, and use of clutter maps. For the airborne environment the clutter characteristics may be somewhat different. Conventional clutter rejection methods may have to be changed and new methods will probably be required to provide useful signal to noise ratios. Various considerations are described. A major thrust has been to evaluate the effect of clutter rejection filtering upon the ability to derive useful information from the post filter radar data. This analysis software is briefly described. Finally, some ideas for future analysis are considered including the use of adaptive filtering for clutter rejection and the estimation of windspeed spatial gradient directly from radar returns as a means of reducing the effects of clutter on the determination of a windshear hazard.

CLUTTER FILTER DESIGN CONSIDERATIONS  
FOR  
AIRBORNE DOPPLER RADAR DETECTION OF WINDSHEAR

Ernest G. Baxa, Jr.  
Clemson University  
Clemson, SC 29634-0915

OUTLINE

- I. The Clutter Problem
  - A. Radar antenna sidelobes causes high clutter levels
  - B. Moving radar platform influences spectrum widths
  - C. Discrete clutter sources in the urban environment
- II. Review of Past Clutter Rejection Research
  - A. Notch filtering at zero Doppler
  - B. Fourier line editing
  - C. Geographical clutter maps
- III. Clutter Rejection for Airbourne Radar
  - A. Notch filter requirements
    - 1. zero gain at zero Doppler
    - 2. transient response short
    - 3. notch width considerations
    - 4. dynamic range requirements
    - 5. non-stationarity
  - B. Fourier line editing
    - 1. mid-band discrete clutter
    - 2. computational load
  - C. Geographical clutter maps
    - 1. poor repeatability
  - D. Antenna Steering
  - E. Adaptive Filters
  - F. Non-conventional Signal Processing
    - 1. estimating windspeed gradient directly
    - 2. hazard detection and estimation
- IV. Effects of Clutter Rejection On Signal Parameter Estimation
  - A. Computer software development
    - 1. filtering in time or frequency domain
    - 2. repeated trials
    - 3. simulated or real data
  - B. Pulse-pair estimation of spectral parameters
    - 1. ideal notch filter
    - 2. simple IIR filters
    - 3. phase response constraints
    - 4. the pulse canceller
- V. Summary and Conclusions

# Clutter Filter Design Considerations For Airborne Doppler Radar Detection of Windshear October 19, 1988

## Clutter Filter Design Considerations for Airborne Doppler Radar Detection of Windshear

by

E.G. Baxa, Jr.  
Clemson University

2nd CMTAW meeting

Radar Systems Laboratory  
Electrical and Computer Engineering  
Clemson University

Oct. 19, 1988

## OUTLINE

- The Clutter Problem
- Review of Past Clutter Rejection Research
- Clutter Rejection for Airborne Radar
- Effects of Clutter Rejection On Signal Parameter Estimation
- Summary and Conclusions

2nd CMTAW meeting


Radar Systems Laboratory  
Electrical and Computer Engineering  
Clemson University

Oct. 19, 1988

# Clutter Filter Design Considerations For Airborne Doppler Radar Detection of Windshear

October 19, 1988

## The Clutter Problem




2nd CMTAW meeting

Radar Systems Laboratory  
Electrical and Computer Engineering  
Clemson University

Oct. 19, 1988

## Simulated Spectra

DFT of 512 Samples of Radar IQ Data





2nd CMTAW meeting



Radar Systems Laboratory  
Electrical and Computer Engineering  
Clemson University

Oct. 19, 1988

# Clutter Filter Design Considerations For Airborne Doppler Radar Detection of Windshear October 19, 1988





# Clutter Filter Design Considerations For Airborne Doppler Radar Detection of Windshear October 19, 1988



# Clutter Filter Design Considerations For Airborne Doppler Radar Detection of Windshear


October 19, 1988



# Clutter Filter Design Considerations For Airborne Doppler Radar Detection of Windshear October 19, 1988

## PULSE-PAIR MEAN WITH IDEAL NOTCH FILTER

Mean Estimate versus True Mean



NYQUIST BW =  $\pm 24.4$  m/s  
TRUE WIDTH SIGMA = 2.0333 m/s  
IDEAL FILTER NOTCH BW = 2.44 m/s


2nd CMTAW meeting

Radar Systems Laboratory  
Electrical and Computer Engineering  
Clemson University

Oct. 19, 1988

## PULSE-PAIR WIDTH WITH IDEAL NOTCH FILTER

Width Estimate versus True Mean



NYQUIST BW =  $\pm 24.4$  m/s  
TRUE WIDTH SIGMA = 2.0333 m/s  
IDEAL FILTER NOTCH BW = 2.44 m/s

2nd CMTAW meeting

Radar Systems Laboratory  
Electrical and Computer Engineering  
Clemson University


Oct. 19, 1988



# Clutter Filter Design Considerations For Airborne Doppler Radar Detection of Windshear October 19, 1988

## PULSE PAIR MEAN WITH 4 m/s IDEAL NOTCH

Mean Estimate versus True Mean



NYQUIST BW =  $\pm 24.4$  m/s  
TRUE WIDTH SIGMA = 2.0333 m/s  
IDEAL FILTER NOTCH BW = 488 m/s


2nd CMTAW meeting

Radar Systems Laboratory  
Electrical and Computer Engineering  
Clemson University

Oct. 19, 1988

## PULSE PAIR WIDTH WITH 4 m/s IDEAL NOTCH

Width Estimate versus True Mean



NYQUIST BW =  $\pm 24.4$  m/s  
TRUE WIDTH SIGMA = 2.0333 m/s  
IDEAL FILTER NOTCH BW = 488 m/s

2nd CMTAW meeting


Radar Systems Laboratory  
Electrical and Computer Engineering  
Clemson University

Oct. 19, 1988

# Clutter Filter Design Considerations For Airborne Doppler Radar Detection of Windshear October 19, 1988

## PULSE-PAIR MEAN WITH BUTTERWORTH NOTCH FILTER

Mean Estimate versus True Mean



NYQUIST BW =  $\pm 24.4$  m/s  
TRUE WIDTH SIGMA = 2.0333 m/s  
 $y(n) = 0.5 * y(n-1) + x(n) - x(n-1)$


2nd CMTAW meeting

Radar Systems Laboratory  
Electrical and Computer Engineering  
Clemson University

Oct. 19, 1988

## PULSE-PAIR WIDTH WITH BUTTERWORTH NOTCH FILTER

Width Estimate versus True Mean



NYQUIST BW = 24.4 m/s  
TRUE WIDTH SIGMA = 2.0333 m/s  
 $y(n) = 0.5 * y(n-1) + x(n) - x(n-1)$

2nd CMTAW meeting


Radar Systems Laboratory  
Electrical and Computer Engineering  
Clemson University

Oct. 19, 1988

# Clutter Filter Design Considerations For Airborne Doppler Radar Detection of Windshear October 19, 1988

## PULSE-PAIR MEAN WITH PULSE CANCELLER

Mean Estimate versus True Mean



NYQUIST BW =  $\pm 24.4$  m/s  
TRUE WIDTH SIGMA = 20333 m/s  
 $y(n) = x(n) - x(n - 1)$


2nd CMTAW meeting

Radar Systems Laboratory  
Electrical and Computer Engineering  
Clemson University

Oct. 19, 1988

## PULSE-PAIR WIDTH WITH PULSE CANCELLER

Width Estimate versus True Mean



NYQUIST BW =  $\pm 24.4$  m/s  
TRUE WIDTH SIGMA = 20333 m/s  
 $y(n) = x(n) - x(n - 1)$

2nd CMTAW meeting

Radar Systems Laboratory  
Electrical and Computer Engineering  
Clemson University

Oct. 19, 1988

**Clutter Filter Design Considerations For  
Airborne Doppler Radar Detection of Windshear  
October 19, 1988**

***SUMMARY***

- **Airborne Environment Has Unique Problems**

- large clutter to signal ratios
- dynamic range requirements
- non-stationarities
- lack of repeatability

- **Optimized Signal Processing Schemes are  
Needed and are Feasible**

2nd CMTAW meeting

Radar Systems Laboratory  
Electrical and Computer Engineering  
Clemson University

Oct. 18, 1988